

## Features

- Power Supply Voltage: 2.5 V to 5.5 V
- Low Supply Current: 50  $\mu$ A per Channel
- High-to-Low Propagation Delay: 120 ns
- Internal Hysteresis Ensures Clean Switching
- Offset Voltage:  $\pm 4$  mV
- Input Bias Current: 30 pA (Typ)
- Input Common-Mode Range Extends 100 mV
- No ESD Diode at both Input Pin to  $+V_S$  and Output Pin to  $+V_S$
- Open-Drain Output for Maximum Flexibility
- LMV331X-S5TR-S, LMV393X-SO1R-S, and LMV393X-VS1R-S are Qualified for Automotive Applications with the AEC- Q100 Reliability Test

## Description


The devices in this series consist of one or two comparators on a single monolithic substrate. The common-mode input voltage range includes ground and power even when operated from a single supply, and the low power supply current drain makes these comparators suitable for battery operation. The devices are designed to directly interface with TTL and CMOS, and the outputs can be connected to other open-collector or open-drain outputs to achieve wired-AND relationships.

The operating temperature range of the devices is from  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ .

## Applications

- Peak and Zero-Crossing Detectors
- Threshold Detectors/Discriminators
- Sensing at the Ground or Supply Line
- Logic Level Shifting or Translation
- Window Comparators
- IR Receivers

### Typical Application Circuit




## Table of Contents

<b>Features</b> .....	<b>1</b>
<b>Applications</b> .....	<b>1</b>
<b>Description</b> .....	<b>1</b>
<b>Typical Application Circuit</b> .....	<b>1</b>
<b>Revision History</b> .....	<b>3</b>
<b>Pin Configuration and Functions</b> .....	<b>4</b>
<b>Specifications</b> .....	<b>6</b>
Absolute Maximum Ratings <sup>(1)</sup> .....	6
ESD, Electrostatic Discharge Protection.....	6
Recommended Operating Conditions.....	6
Thermal Information.....	7
Electrical Characteristics.....	8
Electrical Characteristics (Continued).....	10
Typical Performance Characteristics.....	12
<b>Detailed Description</b> .....	<b>13</b>
Overview.....	13
Functional Block Diagram.....	13
<b>Application and Implementation</b> .....	<b>14</b>
Application Information .....	14
Typical Application.....	15
<b>Tape and Reel Information</b> .....	<b>16</b>
<b>Package Outline Dimensions</b> .....	<b>17</b>
SOT23-5.....	17
SOT353 (SC70-5).....	18
SOP8.....	19
MSOP8.....	20
<b>Order Information</b> .....	<b>21</b>
<b>IMPORTANT NOTICE AND DISCLAIMER</b> .....	<b>22</b>

## Revision History


Date	Revision	Notes
2023-09-03	Rev.A.0	Initial release.
2024-01-22	Rev.A.1	Added the Detailed Description, including some performance description and the Functional Block Diagram. Added the ESD diode description in the Features.
2024-02-15	Rev.A.2	Modified the pin configuration of SOP8. Corrected some typos. The physical object remains unchanged.
2024-12-18	Rev.A.3	The following updates are all about the new datasheet formats or typos, and the actual product remains unchanged. <ul style="list-style-type: none"><li>Updated the Tape and Reel Information.</li></ul>
2025-03-19	Rev.A.4	Added Electrical Characteristics: <ul style="list-style-type: none"><li>Power on time: 40 <math>\mu</math>s.</li></ul>
2025-09-23	Rev.A.5	Added new part numbers: LMV331X-S5TR-S, LMV393X-SO1R-S, and LMV393X-VS1R-S. Updated Electrical Characteristics: <ul style="list-style-type: none"><li><math>V_S = 2.5</math> V, CMRR: changed low limit from 60 dB to 56 dB</li></ul>
2025-11-07	Rev.A.6	Updated Electrical Characteristics: <ul style="list-style-type: none"><li><math>V_S = 2.5</math> V, CMRR low limit 56 dB for LMV393X-VS1R-S, LMV393X-SO1R-S, LMV331X-S5TR-S</li><li><math>V_S = 2.5</math> V, CMRR low limit 60 dB for others</li></ul>

## Pin Configuration and Functions



**Table 1. Pin Functions: LMV331X**

Pin No.		Name	I/O	Description
SOT23-5	SOT353			
1	1	+In	I	Non-inverting input.
2	2	-V <sub>S</sub>	-	Negative power supply.
3	3	-In	I	Inverting input.
4	4	Out	O	Output.
5	5	+V <sub>S</sub>	-	Positive power supply.

**5-V Low-Power Comparators with Open-Drain Output**

**Table 2. Pin Functions: LMV393X**

Pin No.		Name	I/O	Description
SOP8	MSOP8			
1	1	Out A	O	Output.
2	2	-In A	I	Inverting input.
3	3	+In A	I	Non-inverting input.
4	4	-Vs	-	Negative power supply.
5	5	+In B	I	Non-inverting input.
6	6	-In B	I	Inverting input.
7	7	Out B	O	Output.
8	8	+Vs	-	Positive power supply.

## Specifications

### Absolute Maximum Ratings <sup>(1)</sup>

Parameter		Min	Max	Unit
	Supply Voltage, (+V <sub>S</sub> ) – (–V <sub>S</sub> )		6.5	V
	Input Voltage	(–V <sub>S</sub> ) – 0.3	6.5	V
	Input Current: +IN, –IN <sup>(2)</sup>	–10	10	mA
	Output Current: OUT	–10	10	mA
	Output Short-Circuit Duration <sup>(3)</sup>		Thermal Protection	
T <sub>J</sub>	Maximum Junction Temperature		150	°C
T <sub>A</sub>	Operating Temperature Range	–40	125	°C
T <sub>STG</sub>	Storage Temperature Range	–65	150	°C
T <sub>L</sub>	Lead Temperature (Soldering 10 sec)		260	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

(2) The inputs are protected by ESD protection diodes to each power supply. If the input extends more than 500 mV beyond the negative power supply, the input current should be limited to less than 10 mA.

(3) A heat sink may be required to keep the junction temperature below the absolute maximum. This depends on the power supply voltage and how many comparators are shorted. Thermal resistance varies with the amount of PC board metal connected to the package. The specified values are for short traces connected to the leads.

### ESD, Electrostatic Discharge Protection

Parameter		Condition	Level	Unit
HBM	Human Body Model ESD	ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>	4	kV
CDM	Charged Device Model ESD	ANSI/ESDA/JEDEC JS-002 <sup>(2)</sup>	1.5	kV

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### Recommended Operating Conditions

Parameter		Min	Typ	Max	Unit
V <sub>S</sub>	Supply Voltage, (+V <sub>S</sub> ) – (–V <sub>S</sub> )	2.5		5.5	V

---

**5-V Low-Power Comparators with Open-Drain Output****Thermal Information**

Package Type	$\theta_{JA}$	$\theta_{JC}$	Unit
SOT353 (SC70-5)	400	150	°C/W
SOT23-5	250	81	°C/W
SOP8	158	43	°C/W
MSOP8	210	45	°C/W

**5-V Low-Power Comparators with Open-Drain Output**
**Electrical Characteristics**

All test conditions:  $V_S = 5\text{ V}$ ,  $R_{\text{PULL-UP}} = 5.1\text{ k}$ ,  $T_A = 25^\circ\text{C}$ , unless otherwise noted.

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
Power Supply							
I <sub>Q</sub>	Quiescent Current per Comparator	V <sub>CM</sub> = 5 V			50	75	μA
		V <sub>CM</sub> = 5 V, T <sub>A</sub> = −40°C to 125°C				80	μA
PSRR	Power Supply Rejection Ratio	V <sub>S</sub> = 2.5 V to 5 V, V <sub>CM</sub> = 0 V		60	80		dB
		V <sub>S</sub> = 2.5 V to 5 V, V <sub>CM</sub> = 0 V, T <sub>A</sub> = −40°C to 125°C		50			dB
Input Characteristics							
V <sub>OS</sub>	Input Offset Voltage <sup>(1)</sup>	V <sub>CM</sub> = 0 V to 5 V		−4	−0.5	4	mV
		V <sub>CM</sub> = 0 V to 5 V, T <sub>A</sub> = −40°C to 125°C		−5		5	mV
	Input Offset Voltage Drift <sup>(2)</sup>	T <sub>A</sub> = −40°C to 125°C			2		μV/°C
V <sub>HYST</sub>	Input Hysteresis Voltage <sup>(1)</sup>	V <sub>CM</sub> = 0 V to 5 V		1	4.5	10	mV
		V <sub>CM</sub> = 0 V to 5 V, T <sub>A</sub> = −40°C to 125°C				15	mV
	Input Hysteresis Voltage Drift <sup>(2)</sup>	T <sub>A</sub> = −40°C to 125°C			10		μV/°C
I <sub>B</sub>	Input Bias Current <sup>(2)</sup>	V <sub>CM</sub> = 2.5 V			30		pA
		V <sub>CM</sub> = 2.5 V, T <sub>A</sub> = −40°C to 125°C				240	nA
I <sub>OS</sub>	Input Offset Current <sup>(2)</sup>	V <sub>CM</sub> = 2.5 V			30		pA
		V <sub>CM</sub> = 2.5 V, T <sub>A</sub> = −40°C to 125°C				240	nA
C <sub>IN</sub>	Input Capacitance <sup>(4)</sup>	T <sub>A</sub> = 25°C	Differential mode		3.5		pF
			Common mode		6		
V <sub>CM</sub>	Common-Mode Input Voltage Range	T <sub>A</sub> = −40°C to 125°C		(−V <sub>S</sub> ) − 0.1		(+V <sub>S</sub> ) + 0.1	V
CMRR	Common-Mode Rejection Ratio	V <sub>CM</sub> = 0 V to 5 V		60	80		dB
		V <sub>CM</sub> = 0 V to 5 V, T <sub>A</sub> = −40°C to 125°C		50			dB
Output Characteristics							
I <sub>OH</sub>	High-Level Output Current <sup>(2)</sup>	V <sub>OH</sub> = 5 V, V <sub>ID</sub> = 1 V			1		nA
		V <sub>OH</sub> = 5 V, V <sub>ID</sub> = 1 V, T <sub>A</sub> = −40°C to 125°C			100		nA
V <sub>OL</sub>	Low-Level Output Voltage	I <sub>OL</sub> = 1 mA, V <sub>ID</sub> = −1 V			10	20	mV
		I <sub>OL</sub> = 1 mA, V <sub>ID</sub> = −1 V, T <sub>A</sub> = −40°C to 125°C				50	mV
I <sub>OL</sub>	Low-Level Output Current	V <sub>OL</sub> = 1.5 V, V <sub>ID</sub> = −1 V		80	120		mA
		V <sub>OL</sub> = 1.5 V, V <sub>ID</sub> = −1 V, T <sub>A</sub> = −40°C to 125°C		50			mA
I <sub>SC</sub>	Output Short-Circuit Current	Sink current		85	125		mA
		Sink current, T <sub>A</sub> = −40°C to 125°C		70			mA



**5-V Low-Power Comparators with Open-Drain Output**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>Switching Characteristics, <math>T_A = -40^{\circ}\text{C}</math> to <math>125^{\circ}\text{C}</math> <sup>(3)</sup></b>						
$T_{PLH}$	Propagation Delay Time, Low to High	$\Delta V_{IN} = 1\text{ V}$ , $V_{CM} = 0\text{ V}$ , 100-mV overdrive, $C_L = 15\text{ pF}$ <sup>(2)</sup>		120	180	ns
		$\Delta V_{IN} = 1\text{ V}$ , $V_{CM} = 0\text{ V}$ , 20-mV overdrive, $C_L = 15\text{ pF}$ <sup>(2)</sup>		220		ns
$T_{PHL}$	Propagation Delay Time, High to Low	$\Delta V_{IN} = 1\text{ V}$ , $V_{CM} = 0\text{ V}$ , 100-mV overdrive, $C_L = 15\text{ pF}$ <sup>(2)</sup>		110	170	ns
		$\Delta V_{IN} = 1\text{ V}$ , $V_{CM} = 0\text{ V}$ , 20-mV overdrive, $C_L = 15\text{ pF}$ <sup>(2)</sup>		222		ns
$T_R$	Rise Time	$C_L = 15\text{ pF}$ <sup>(2)(5)</sup>		181		ns
$T_F$	Fall Time	<sup>(2)(5)</sup>		0.81		ns
$T_{ON}$	Power On Time	<sup>(2)</sup>		40		$\mu\text{s}$

(1) The input offset voltage is the average of the input-referred trip points. The input hysteresis is the difference between the input-referred trip points.

(2) Provided by bench tests and design simulation.

(3) Delay time is measured from the mid-point of the input to the mid-point of the output.

(4) Provided by design simulation.

(5) Measured between 10% of  $V_S$  and 90% of  $V_S$ .

**5-V Low-Power Comparators with Open-Drain Output**
**Electrical Characteristics (Continued)**

All test conditions:  $V_S = 2.5\text{ V}$ ,  $R_{PULL-UP} = 5.1\text{ k}$ ,  $T_A = 25^\circ\text{C}$ , unless otherwise noted.

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
Power Supply							
I <sub>Q</sub>	Quiescent Current per Comparator	V <sub>CM</sub> = 2.5 V			53	90	μA
		V <sub>CM</sub> = 2.5 V, T <sub>A</sub> = −40°C to 125°C				100	μA
Input Characteristics							
V <sub>OS</sub>	Input Offset Voltage <sup>(1)</sup>	V <sub>CM</sub> = 0 V to 2.5 V		−4	−0.5	4	mV
		V <sub>CM</sub> = 0 V to 2.5 V, T <sub>A</sub> = −40°C to 125°C		−5		5	mV
	Input Offset Voltage Drift <sup>(2)</sup>	T <sub>A</sub> = −40°C to 125°C			2		μV/°C
V <sub>HYST</sub>	Input Hysteresis Voltage <sup>(1)</sup>	V <sub>CM</sub> = 0 V to 2.5 V		1	4.5	10	mV
		V <sub>CM</sub> = 0 V to 2.5 V, T <sub>A</sub> = −40°C to 125°C				15	mV
	Input Hysteresis Voltage Drift <sup>(2)</sup>	T <sub>A</sub> = −40°C to 125°C			10		μV/°C
I <sub>B</sub>	Input Bias Current <sup>(2)</sup>	V <sub>CM</sub> = 1.25 V			30		pA
		V <sub>CM</sub> = 1.25 V, T <sub>A</sub> = −40°C to 125°C				240,000	pA
I <sub>OS</sub>	Input Offset Current <sup>(2)</sup>	V <sub>CM</sub> = 1.25 V			2		pA
		V <sub>CM</sub> = 1.25 V, T <sub>A</sub> = −40°C to 125°C				10	pA
C <sub>IN</sub>	Input Capacitance <sup>(4)</sup>	T <sub>A</sub> = 25°C	Differential mode		3.5		pF
			Common mode		6		
V <sub>CM</sub>	Common-Mode Input Voltage Range	T <sub>A</sub> = −40°C to 125°C		(−V <sub>S</sub> ) − 0.1		(+V <sub>S</sub> ) + 0.1	V
CMRR	Common-Mode Rejection Ratio	V <sub>CM</sub> = 0 V to 2.5 V		60	75		dB
		V <sub>CM</sub> = 0 V to 2.5 V, LMV393X-VS1R-S, LMV393X-SO1R-S, LMV331X-S5TR-S		56	75		dB
		V <sub>CM</sub> = 0 V to 2.5 V, T <sub>A</sub> = −40°C to 125°C		50			dB
Output Characteristics							
I <sub>OH</sub>	High-Level Output Current <sup>(4)</sup>	V <sub>OH</sub> = 2.5 V, V <sub>ID</sub> = 1 V			10		nA
		V <sub>OH</sub> = 2.5 V, V <sub>ID</sub> = 1 V, T <sub>A</sub> = −40°C to 125°C					nA
V <sub>OL</sub>	Low-Level Output Voltage	I <sub>OL</sub> = 1 mA, V <sub>ID</sub> = −1 V			15	20	mV
		I <sub>OL</sub> = 1 mA, V <sub>ID</sub> = −1 V, T <sub>A</sub> = −40°C to 125°C				50	mV
I <sub>OL</sub>	Low-Level Output Current <sup>(4)</sup>	V <sub>OL</sub> = 1.5 V, V <sub>ID</sub> = 1 V			45		mA
		V <sub>OL</sub> = 1.5 V, V <sub>ID</sub> = 1 V, T <sub>A</sub> = −40°C to 125°C					mA
I <sub>SC</sub>	Output Short-Circuit Current	Sink current		42	50		mA
		Sink current, T <sub>A</sub> = −40°C to 125°C		35			mA
Switching Characteristics, T <sub>A</sub> = −40°C to 125°C <sup>(3)</sup>							

**5-V Low-Power Comparators with Open-Drain Output**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$T_{PLH}$	Propagation Delay Time, Low to High	$\Delta V_{IN} = 1\text{ V}$ , $V_{CM} = 0\text{ V}$ , 100-mV overdrive, $C_L = 15\text{ pF}$ <sup>(4)</sup>		158	230	ns
		$\Delta V_{IN} = 1\text{ V}$ , $V_{CM} = 0\text{ V}$ , 20-mV overdrive, $C_L = 15\text{ pF}$ <sup>(4)</sup>		280		ns
$T_{PHL}$	Propagation Delay Time, High to Low	$\Delta V_{IN} = 1\text{ V}$ , $V_{CM} = 0\text{ V}$ , 100-mV overdrive, $C_L = 15\text{ pF}$ <sup>(4)</sup>		120	230	ns
		$\Delta V_{IN} = 1\text{ V}$ , $V_{CM} = 0\text{ V}$ , 20-mV overdrive, $C_L = 15\text{ pF}$ <sup>(4)</sup>		223		ns
$T_R$	Rise Time	$C_L = 15\text{ pF}$ <sup>(4)(5)</sup>		181		ns
$T_F$	Fall Time	<sup>(2)(5)</sup>		1.5		ns

(1) The input offset voltage is the average of the input-referred trip points. The input hysteresis is the difference between the input-referred trip points.

(2) Provided by bench tests and design simulation.

(3) Delay time is measured from the mid-point of the input to the mid-point of the output.


(4) Provided by design simulation.

(5) Measured between 10% of  $V_S$  and 90% of  $V_S$ .


## 5-V Low-Power Comparators with Open-Drain Output

### Typical Performance Characteristics


All test conditions:  $V_S = 5\text{ V}$ ,  $V_{CM} = 0\text{ V}$ ,  $R_{PULL-UP} = 5.1\text{ k}$ , unless otherwise noted.




**Figure 1. Supply Current vs. Supply Voltage, Output High (Single Channel)**



**Figure 2. Supply Current vs. Temperature (Dual Channel)**



**Figure 3. Propagation Delay, Low to High**



**Figure 4. Propagation Delay, High to Low**

## Detailed Description

### Overview

The LMV331X and LMV393X devices feature 158-ns response time and include 4.5 mV of internal hysteresis for improved noise immunity with an input common-mode range that extends 0.1 V beyond the power supply rails, having the ability to operate from 2.5 V to 5.5 V on the supply pin.

The open-drain output allows the logic high voltage ( $V_{OH}$ ) of the output to be configured, or be used in AND functionality. Without the ESD diode between the output pin and the  $+V_S$  pin, the output pull-up resistor can be connected to the voltage level, independent of the positive supply voltage for level-shifting applications.

### Functional Block Diagram




Figure 5. Functional Block Diagram

## Application and Implementation

### Note

Information in the following application sections is not part of the 3PEAK's component specification and 3PEAK does not warrant its accuracy or completeness. 3PEAK's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

## Application Information

### Power Supply Layout and Bypass

The power supply pins of LMV331X and LMV393X families should have local bypass capacitors (i.e., 0.01  $\mu\text{F}$  to 0.1  $\mu\text{F}$ ) within 2 mm for high-frequency performance. They can also use a bulk capacitor (i.e., 1  $\mu\text{F}$  or larger) within 100 mm to provide large and slow currents. This bulk capacitor can be shared with other analog parts.

A good ground layout improves performance by decreasing the amount of stray capacitance and noise at the inputs and outputs of the comparator. To decrease stray capacitance, minimize PCB lengths and resistor leads, and place external components to the pins of the comparator as close as possible.

### Operation Outside of the Common Input Voltage Range

A list of input voltage situations and the corresponding outcomes are as follows:

1. When both  $-IN$  and  $+IN$  are within the common-mode range:
  - a. If the voltage at the  $-IN$  pin is higher than the voltage at the  $+IN$  pin and the offset voltage, the output is low, and the output MOSFET is sinking current.
  - b. If the voltage at the  $-IN$  pin is lower than the voltage at the  $+IN$  pin and the offset voltage, the output is high impedance.
2. When the voltage at the  $-IN$  pin is higher than the common-mode voltage range and the voltage at the  $+IN$  pin is within the common-mode voltage range, the output is low, and the output MOSFET is sinking current.
3. When the voltage at the  $+IN$  pin is higher than the common-mode voltage range and the voltage at the  $-IN$  pin is within the common-mode voltage range, the output is high impedance.
4. When the voltage at the  $-IN$  and  $+IN$  pins are both higher than the common-mode voltage range, the output is in an uncertain state.

## Typical Application

### IR Receiver

The device is an ideal candidate to be used as an infrared receiver shown in [Figure 6](#). The infrared photo diode creates a current relative to the amount of infrared light present. The current creates a voltage across  $R_D$ . When this voltage level crosses the voltage applied by the voltage divider to the inverting input, the output transitions. Optional  $R_O$  provides additional hysteresis for noise immunity.





Figure 6. Typical Application Circuit

## Tape and Reel Information




Order Number	Package	D1 (mm)	W1 (mm)	A0 (mm) <sup>(1)</sup>	B0 (mm) <sup>(1)</sup>	K0 (mm) <sup>(1)</sup>	P0 (mm)	W0 (mm)	Pin1 Quadrant
LMV331X-SC5R	SOT353 (SC70-5)	178	12.1	2.4	2.5	1.2	4	8	Q3
LMV393X-VS1R	MSOP8	330	17.6	5.3	3.4	1.3	8	12	Q1
LMV393X-VS1R-S	MSOP8	330	17.6	5.3	3.4	1.3	8	12	Q1
LMV393X-SO1R	SOP8	330	17.6	6.5	5.4	2	8	12	Q1
LMV331X-S5TR	SOT23-5	179	12	3.3	3.25	1.4	4	8	Q3
LMV331X-S5TR-S	SOT23-5	179	12	3.3	3.25	1.4	4	8	Q3





(1) The value is for reference only. Contact the 3PEAK factory for more information.



## Package Outline Dimensions

### SOT23-5




**SOT353 (SC70-5)**
**Package Outline Dimensions**
**SC5(SOT353-5-A)**


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.850	1.100	0.033	0.043
A1	0.000	0.100	0.000	0.004
A2	0.800	1.000	0.031	0.039
b	0.150	0.350	0.006	0.014
c	0.110	0.230	0.004	0.009
D	2.000	2.200	0.079	0.087
E	2.150	2.450	0.085	0.096
E1	1.150	1.350	0.045	0.053
e	0.650 BSC		0.026 BSC	
L	0.260	0.460	0.010	0.018
$\theta$	0	8°	0	8°

**NOTES**





1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

**SOP8**
**Package Outline Dimensions**
**SO1(SOP-8-A)**


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	1.350	1.750	0.053	0.069
A1	0.050	0.250	0.002	0.010
A2	1.250	1.550	0.049	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.007	0.010
D	4.700	5.100	0.185	0.201
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
e	1.270 BSC		0.050 BSC	
L	0.400	1.000	0.016	0.039
θ	0	8°	0	8°

**NOTES**

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

**MSOP8**
**Package Outline Dimensions**
**VS1(MSOP-8-A)**


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.800	1.100	0.031	0.043
A1	0.020	0.150	0.001	0.006
A2	0.750	0.950	0.030	0.037
b	0.250	0.380	0.010	0.015
c	0.090	0.230	0.004	0.009
D	2.900	3.100	0.114	0.122
E	4.700	5.100	0.185	0.201
E1	2.900	3.100	0.114	0.122
e	0.650 BSC		0.026 BSC	
L	0.400	0.800	0.016	0.031
θ	0	8°	0	8°

**NOTES**

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

## Order Information

Order Number	Operating Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity	Eco Plan
LMV331X-SC5R	-40 to 125°C	SOT353 (SC70-5)	A16	1	Tape and Reel, 3000	Green
LMV393X-VS1R	-40 to 125°C	MSOP8	V393X	2	Tape and Reel, 3000	Green
LMV393X-VS1R-S <sup>(1)</sup> (2)	-40 to 125°C	MSOP8	V393X	2	Tape and Reel, 3000	Green
LMV393X-SO1R	-40 to 125°C	SOP8	V393X	2	Tape and Reel, 4000	Green
LMV393X-SO1R-S <sup>(1)</sup> (2)	-40 to 125°C	SOP8	V393X	2	Tape and Reel, 4000	Green
LMV331X-S5TR	-40 to 125°C	SOT23-5	A16	2	Tape and Reel, 3000	Green
LMV331X-S5TR-S <sup>(1)</sup>	-40 to 125°C	SOT23-5	A16	2	Tape and Reel, 3000	Green

(1) Passed AEC-Q100 Reliability Test.

(2) For future products, contact the 3PEAK factory for more information and samples.

**Green:** 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

## **IMPORTANT NOTICE AND DISCLAIMER**

**Copyright**© 3PEAK 2012-2025. All rights reserved.

**Trademarks.** Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

**Performance Information.** Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

**Disclaimer.** 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.